



Technical Data Sheet

X-5 Solvent

Product Description X-5 Solvent is a multi-purpose thinning solvent blend designed specifically for **EPiC PolyCryl, PolyGlo, UltraGlo, PR Sealer, Chlorinated Rubber** and **NuPool Chlorinated Rubber** products.
X-5 Solvent can also be used for clean-up of all equipment when using **EPiC PolyCryl, PolyGlo, UltraGlo, PR Sealer, Chlorinated Rubber** and **NuPool Chlorinated Rubber** Top coats.

Safety Precautions: Observe all Occupation Health and Safety (OH&S) precautions. Refer to the relevant Safety Data Sheets (SDS) for product safety related information.
For further information and support: **Nutech Paint 03 9770 3000**
www.nutechpaint.com.au

KEEP AWAY FROM HEAT, FLAME AND SOURCES OF IGNITION.

- Vapours are heavier than air. Keep container closed.
- Use only with adequate ventilation.
- Avoid contact with eyes, skin and clothing.
- Wash thoroughly after handling.
- Avoid breathing vapours.
- DO NOT take internally.
- Use impervious gloves, eye protection and if the TLV is exceeded or used in a poorly ventilated area, use NIOSH/MSHA approved respiratory protection in accordance with applicable Federal, state and local regulations

Provisions:

Chemical Type: Blended Thinning Solvent for **EPiC PolyCryl, PolyGlo UltraGlo, PR Sealer, Chlorinated Rubber 25%** and **NuPool Chlorinated Rubber**.

Product Attributes Per Cent Volatiles (VOC): 100%
Solubility: Solvent
Minimum Film Forming Temperature: N/A
Minimum Dry Film Thickness: N/A

Typical Applications Thinning and cleaning of **EPiC PolyCryl, PR Sealer, Chlorinated Rubber 25%** and **NuPool Chlorinated Rubber**

Appearance Colourless thin liquid

Coverage / Spread Rate N/A

Packaging 1L, 2L, 4L, 10L, 20L

Storage Cool, dry location. Avoid contact with direct sunlight and heat



Substrate	Refer EPiC PolyCryl, PolyGlo UltraGlo, PR Sealer, Chlorinated Rubber 25% and NuPool
Recommendations:	Chlorinated Rubber TDS
Mixing/ Thinning	Maximum Thinner dilution for: EPiC PolyCryl, PolyGlo UltraGlo, PR Sealer, Chlorinated Rubber 25% and NuPool Chlorinated Rubber; Brush/Roller 1st Coat: Bare concrete and masonry surfaces thin 20% - 25% for excellent penetration and adhesion. Brush/Roller 2nd Coat: Nil Spray: 10% - 15%
Drying Time	Touch Dry: N/A
Recoat	N/A
Hard Cure:	N/A
Clean Up	Protecting Our Environment is important to Nutech Paints: Clean up with X-5 Solvent or dispose of equipment. Do not pour leftover paint down drains or in rubbish bins. Unwanted Thinners should be kept in a sealed container and then disposed of via specialised waste collection services. Empty paint containers should be left open in a well ventilated area to dry out. Dispose of empty paint containers in accordance with local authority's guidelines. Always check with your local council first.
First Aid	SEEK IMMEDIATE MEDICAL ATTENTION. Refer to the appropriate Nutech Safety Data Sheet (SDS) for further information. For medical emergencies only, call: 000 <ul style="list-style-type: none">• In case of eye contact, flush thoroughly with water for at least 15 minutes.• In case of skin contact, wash affected areas with soap and water. If irritation persists.• Remove and wash contaminated clothing.• If inhalation causes physical discomfort, remove to fresh air.• If discomfort persists, or any breathing difficulty occurs or if swallowed seek medical advice.



Warranty

Nutech warrants its products to be free from defects in material and workmanship. Nutech's sole obligation and Buyer's exclusive remedy in connection with the products shall be limited, at Nutech's option, to either replacement of products not conforming to this Warranty or credit to Buyer's account in the invoiced amount of the nonconforming products.

Any claim under this Warranty must be made by Buyer to Nutech in writing within five (5) days of Buyer's discovery of the claimed defect, but in no event later than the expiration of the applicable shelf life, or one year from the delivery date, whichever is earlier. Buyer's failure to notify Nutech of such non-conformance as required herein shall bar Buyer from recovery under this Warranty.

Nutech makes no other warranties concerning the product. No other warranties, whether express, implied, or statutory, such as warranties of merchantability or fitness for a particular purpose, shall apply. In no event shall Nutech be liable for consequential or incidental damages.

Any recommendation or suggestion relating to the use of the products made by Nutech, whether in its technical literature, or in response to specific inquiry, or otherwise, is based on data believed to be reliable; however, the products and information are intended for use by Buyers having requisite skill and know-how in the industry, and therefore it is for Buyer to satisfy itself of the suitability of the products for its own particular use and it shall be deemed that Buyer has done so, at its sole discretion and risk. Variation in environment, changes in procedures of use, or extrapolation of data may cause unsatisfactory results.

Limitation of Liability

Nutech's liability on any claim of any kind, including claims based upon Nutech's negligence or strict liability, for any loss or damage arising out of, connected with, or resulting from the use of the products, shall in no case exceed the purchase price allocable to the products or part thereof which gives rise to the claim. In no event shall Nutech be liable for consequential or incidental damages.

Disclaimer

The information given on this data sheet is based on many years' experience and is correct to the best of our knowledge. However, since the use of our product, surface conditions, weather and a number of other factors are completely beyond our control, we can only be responsible for the quality of our product at the time of dispatch. For more information please contact our Company. As this information is of a general nature, we cannot assume any responsibility in individual cases.'

The information contained in this data sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.

Nutech

Nutech Paint
PTY LTD

☎03 9770 3000

✉sales@nutech.com.au

www.nutechpaint.com.au