



HD Cleaner

General purpose degreaser, cleaner and sealer remover.

DESCRIPTION

HD Cleaner is a general purpose degreaser and cleaner designed to remove grease, grime and dirt from a variety of surfaces such as metal, wood and concrete.

HD Cleaner may also be used to remove cured sealer coatings.

ADVANTAGES

HD Cleaner delivers the following advantages;

- Fast acting.
- Rinsable with water.

AREAS OF USE

HD Cleaner is suitable for use in the following areas;

- Degrease masonry surfaces prior to sealing.
- Degrease metal prior to priming.
- Remove cured sealer coatings
- Paint brush restorer & cleaner.
- Degreasing of car engines.

SUBSTRATES

HD Cleaner is suitable for application on;

- Concrete
- Exposed Aggregate Panels
- Steel
- Masonry

TECHNICAL DATA (@ 25°C)

Coverage: (per coat) 10 - 12m²/L

Colour: Clear

Clean Up: Water

Shelf Life: 12 Months

APPLICATION

- A test patch is recommended before full application.
- Work in manageable areas at a time.
- Protect surrounding areas from over-spray etc.

For spot cleaning & degreasing of un-coated exterior surfaces:

- Use neat.
- Apply by brush or cloth a liberal quantity of product to the area. Scrub and rinse thoroughly until foaming stops. Rinsing with a pressure washer is recommended.
- Multiple applications may be required for tough contaminants.
- Allow substrate to completely dry before application of any coatings.
- Clean all application equipment with water.

For general cleaning of un-coated exterior surfaces:

- Use diluted, 1 part product to 2 parts water.
- Apply by brush, roller or watering can and gently scrub the surface to loosen dirt and contaminants.
- After 10 minutes, thoroughly rinse the area until foaming stops. Rinsing with a pressure washer is recommended.
- Multiple applications may be required if surface contaminants remain.
- Allow substrate to completely dry before application of any coatings.
- Clean all application equipment with water.

HD Cleaner

General purpose degreaser, cleaner and sealer remover.

For the removal of cured sealer:

- Apply by brush or roller a liberal quantity of un-diluted product to the area. Gently agitate the surface with the brush or roller until the cured sealer re-emulsifies. This will take only a matter of seconds to minutes, dependent upon the age and thickness of the coating being removed.
- Immediately pressure wash the treated area before moving on to the next area. Thoroughly rinse until foaming stops. Remove standing water from the next area of application before applying product.
- If the coating has been applied to internal areas or areas where pressure washing is not practical, remove re-emulsified coating with rags and then thoroughly rinse and mop to remove all residues.
- Multiple applications may be required for highly porous surfaces and / or thick sealer applications.
- Continue this process until the entire area has been completed.
- Allow substrate to completely dry before application of any coatings.
- Clean all application equipment with water.

ANCILLARY PRODUCTS

- Crommelin® Contractor Membrane Applicator Brush – 100mm, 75mm

CLEAN UP

- Wash all equipment in warm water and a small amount of detergent immediately after use.

PRECAUTIONS

- HD Cleaner will soften painted surfaces and some plastics.
- It is recommended to test the product on the substrate prior to doing the whole project.

Crommelin® and other marks followed by ® are registered trademarks.

Any advice, recommendation, information, assistance or service provided by Crommelin® in relation to its products or their use is given in good faith, however is provided without responsibility or liability.

Customers need to undertake their own assessment to determine the suitability of a product for the intended use. As the performance of any product is subject to a wide variety of different surface types as well as environmental and surface-specific conditions, it is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs as required on the specific surface.

Crommelin® also reserves the right to update information without prior notice, to reflect ongoing research and product development.

WARRANTIES

Please contact your Crommelin® representative, or the Crommelin® technical support team for detailed specifications applicable to your project and warranty requirements.

TRANSPORT AND STORAGE

- Size: 15L
- Weight: 15kg
- DG Class: 3
- Flash Point: 13°C
- UN Number: 1993
- Cool and Dry Storage
- Poisons Schedule: Not Applicable
- Hazchem Code: 3Y(E)

SAFETY AND FIRST AID

HD Cleaner Safety Data Sheet is available from Crommelin® upon request.

Safety

- Ensure good ventilation and avoid breathing vapours.
- Avoid skin and eye contact. Wear gloves and eye protection. Remove splashes on skin immediately and remove contaminated clothing.
- Keep out of reach of children.
- Keep container sealed when not in use.
- Do not swallow.

First Aid

- If poisoning occurs, contact a doctor or poisons information centre: Ph. 13 11 26.
- If swallowed, do not induce vomiting. Give a glass of water to drink.
- If in eyes, hold eyes open and flood with water for at least 15 minutes.
- If not breathing, apply artificial respiration.