

SAFETY DATA SHEET

Sikabond-105 ContactFix



Version
2.0

Revision Date:
13.02.2020

SDS Number:
000000613214

Date of last issue: 27.05.2019
Date of first issue: 14.12.2016

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sikabond-105 ContactFix

Product code : 000000613214

Manufacturer or supplier's details

Company : Sika Australia Pty. Ltd.
55 Elizabeth Street
Wetherill Park, NSW 2164

Telephone : +61 2 9725 11 45

Telefax : +61 2 9725 33 30


Emergency telephone number : +61 1800 033 111

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

- Flammable liquids : Category 2
- Skin corrosion/irritation : Category 2
- Serious eye damage/eye irritation : Category 2A
- Reproductive toxicity : Category 2
- Specific target organ toxicity - single exposure : Category 3 (Central nervous system)
- Specific target organ toxicity - repeated exposure (Inhalation) : Category 2
- Aspiration hazard : Category 1
- Long-term (chronic) aquatic hazard : Category 2

GHS label elements

- Hazard pictograms : 
- Signal word : Danger
- Hazard statements : H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.

SAFETY DATA SHEET

Sikabond-105 ContactFix



Version
2.0

Revision Date:
13.02.2020

SDS Number:
000000613214

Date of last issue: 27.05.2019
Date of first issue: 14.12.2016

Precautionary statements :

H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H361 Suspected of damaging fertility or the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure if inhaled.
H411 Toxic to aquatic life with long lasting effects.

Prevention:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/ eye protection/ face protection.
P281 Use personal protective equipment as required.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.
P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P331 Do NOT induce vomiting.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.
P391 Collect spillage.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

SAFETY DATA SHEET

Sikabond-105 ContactFix



Version
2.0

Revision Date:
13.02.2020

SDS Number:
000000613214

Date of last issue: 27.05.2019
Date of first issue: 14.12.2016

P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Solvent naphtha (petroleum), light aliph.; Low boiling point naphtha	64742-89-8	>= 30 -< 60
toluene	108-88-3	>= 10 -< 20
acetone	67-64-1	>= 10 -< 20
n-hexane	110-54-3	>= 3 -< 10

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : Risk of serious damage to the lungs (by aspiration).
irritant effects
Aspiration may cause pulmonary oedema and pneumonitis.
Excessive lachrymation
Dermatitis
Loss of balance
Vertigo
See Section 11 for more detailed information on health effects and symptoms.

SAFETY DATA SHEET

Sikabond-105 ContactFix



Version
2.0

Revision Date:
13.02.2020

SDS Number:
000000613214

Date of last issue: 27.05.2019
Date of first issue: 14.12.2016

Notes to physician : May be fatal if swallowed and enters airways.
Causes skin irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness.
Suspected of damaging fertility or the unborn child.
May cause damage to organs through prolonged or repeated exposure if inhaled.
: Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : Water

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

Specific extinguishing methods : Use water spray to cool unopened containers.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Hazchem Code : •3YE

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Remove all sources of ignition.
Deny access to unprotected persons.

Environmental precautions : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Use explosion-proof equipment.
Keep away from heat/ sparks/ open flames/ hot surfaces. No

SAFETY DATA SHEET

Sikabond-105 ContactFix



Version
2.0

Revision Date:
13.02.2020

SDS Number:
000000613214

Date of last issue: 27.05.2019
Date of first issue: 14.12.2016

- smoking.
Take precautionary measures against electrostatic discharges.
- Advice on safe handling : Do not breathe vapours or spray mist.
Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharge.
Open drum carefully as content may be under pressure.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Follow standard hygiene measures when handling chemical products
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.
- Conditions for safe storage : Store in original container.
Store in cool place.
Keep in a well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Store in accordance with local regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Solvent naphtha (petroleum), light aliph.; Low boiling point naphtha	64742-89-8	TWA	900 mg/m ³	AU OEL
toluene	108-88-3	TWA	50 ppm 191 mg/m ³	AU OEL
	Further information: Skin absorption			
		STEL	150 ppm 574 mg/m ³	AU OEL
	Further information: Skin absorption			
acetone	67-64-1	TWA	500 ppm 1,185 mg/m ³	AU OEL
		STEL	1,000 ppm 2,375 mg/m ³	AU OEL
n-hexane	110-54-3	TWA	20 ppm 72 mg/m ³	AU OEL

SAFETY DATA SHEET

Sikabond-105 ContactFix



Version
2.0

Revision Date:
13.02.2020

SDS Number:
000000613214

Date of last issue: 27.05.2019
Date of first issue: 14.12.2016

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
chloroprene (stabilised)	126-99-8	TWA	10 ppm 36 mg/m ³	AU OEL
Further information: Category 1B (Carc. 1B) Presumed to have carcinogenic potential for humans, Skin absorption				

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
toluene	108-88-3	Toluene	In blood	Prior to last shift of work-week	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g Creatinine	ACGIH BEI
acetone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI
n-hexane	110-54-3	2,5-Hexanedi-one	Urine	End of shift at end of workweek	0.4 mg/l	ACGIH BEI

Appropriate engineering controls : Use adequate ventilation and/or engineering controls to prevent exposure to vapours.
Avoid vapor formation.
Provide appropriate exhaust ventilation at places where vapor is formed.

Personal protective equipment

Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

SAFETY DATA SHEET

Sikabond-105 ContactFix



Version
2.0

Revision Date:
13.02.2020

SDS Number:
000000613214

Date of last issue: 27.05.2019
Date of first issue: 14.12.2016

Hand protection	:	organic vapor filter (Type A) Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Follow AS/NZS 1337.1 Recommended: Butyl rubber/nitrile rubber gloves. Contaminated gloves should be removed.
Eye protection	:	Safety glasses
Skin and body protection	:	Protective clothing (e.g. safety shoes, long-sleeved working clothing, long trousers) Follow AS 2210:3 Protective clothing needs to be made of cotton.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Colour	:	yellow
Odour	:	hydrocarbon-like
Odour Threshold	:	No data available
pH	:	Not applicable
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	-30 °C (-22 °F) (Method: closed cup)
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	7 %(V)
Lower explosion limit / Lower flammability limit	:	1 %(V)
Vapour pressure	:	150 hPa
Relative vapour density	:	No data available
Density	:	0.8 g/cm ³ (20 °C (68 °F))
Solubility(ies)	:	
Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available

SAFETY DATA SHEET

Sikabond-105 ContactFix



Version 2.0 Revision Date: 13.02.2020 SDS Number: 000000613214 Date of last issue: 27.05.2019
Date of first issue: 14.12.2016

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

 Viscosity, dynamic : No data available

 Viscosity, kinematic : > 7 mm²/s (40 °C (104 °F))

Explosive properties : No data available

Oxidizing properties : No data available

|| Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 77 %

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reactions : Stable under recommended storage conditions.
Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : see section 7.

Hazardous decomposition products : chloroprene (stabilised)

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

|| acetone:

Acute oral toxicity : LD50 Oral (Rat): 5,800 mg/kg

Acute inhalation toxicity : LC50 (Rat): 76 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rabbit): 20,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

SAFETY DATA SHEET

Sikabond-105 ContactFix



Version
2.0

Revision Date:
13.02.2020

SDS Number:
000000613214

Date of last issue: 27.05.2019
Date of first issue: 14.12.2016

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Chronic toxicity

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

STOT - single exposure

May cause drowsiness or dizziness.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure if inhaled.

Aspiration toxicity

May be fatal if swallowed and enters airways.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

|| acetone:

Toxicity to fish : LC50 (Fish): > 5,000 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia (water flea)): 12.700 mg/l
aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 530
plants mg/l
Exposure time: 96 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

SAFETY DATA SHEET

Sikabond-105 ContactFix



Version
2.0

Revision Date:
13.02.2020

SDS Number:
000000613214

Date of last issue: 27.05.2019
Date of first issue: 14.12.2016

Other adverse effects

Product:

Additional ecological information : Toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

If potential for exposure exists refer to Section 8 for specific personal protective equipment.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 1133
Proper shipping name : Adhesives
Class : 3
Packing group : II
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 364
Packing instruction (passenger aircraft) : 353

IMDG-Code

UN number : UN 1133
Proper shipping name : ADHESIVES
Class : 3
Packing group : II
Labels : 3
EmS Code : F-E, S-D
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

ADG

UN number : UN 1133
Proper shipping name : ADHESIVES

SAFETY DATA SHEET

Sikabond-105 ContactFix



Version 2.0	Revision Date: 13.02.2020	SDS Number: 000000613214	Date of last issue: 27.05.2019 Date of first issue: 14.12.2016
----------------	------------------------------	-----------------------------	---

Class : 3
Packing group : II
Labels : 3
Hazchem Code : •3YE

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard for the Uniform Scheduling of Medicines and Poisons : Schedule 5

Standard for the Uniform Scheduling of Medicines and Poisons : No poison schedule number allocated

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors : Not applicable

Prohibition/Licensing Requirements : There is no applicable prohibition or notification/licensing requirements, including for carcinogens under Commonwealth, State or Territory legislation.

The components of this product are reported in the following inventories:

AICS : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Revision Date : 13.02.2020
Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
AU OEL : Australia. Workplace Exposure Standards for Airborne Contaminants.

AU OEL / TWA : Exposure standard - time weighted average
AU OEL / STEL : Exposure standard - short term exposure limit

ADG : Australian Dangerous Goods Code.
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road

CAS : Chemical Abstracts Service

SAFETY DATA SHEET

Sikabond-105 ContactFix



Version 2.0	Revision Date: 13.02.2020	SDS Number: 000000613214	Date of last issue: 27.05.2019 Date of first issue: 14.12.2016
----------------	------------------------------	-----------------------------	---

DNEL	: Derived no-effect level
EC50	: Half maximal effective concentration
GHS	: Globally Harmonized System
IATA	: International Air Transport Association
IMDG	: International Maritime Code for Dangerous Goods
LD50	: Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	: Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	: International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	: Occupational Exposure Limit
PBT	: Persistent, bioaccumulative and toxic
PNEC	: Predicted no effect concentration
REACH	: Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	: Substances of Very High Concern
vPvB	: Very persistent and very bioaccumulative

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: aus.sika.com

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

|| Changes as compared to previous version !

AU / EN